



FLIR TG165

Imaging IR Thermometer

The FLIR TG165 Imaging IR Thermometer bridges the gap between single spot infrared thermometers and FLIR's legendary thermal cameras. Equipped with FLIR's exclusive Lepton® micro thermal sensor, the TG165 lets you see the heat so you know where to reliably measure it. Easily find unseen hot and cold spots for instant troubleshooting, and store images and data to show customers and include in reports.

See the Heat™ - Speed Troubleshooting

FLIR's Innovative Lepton® IR Imaging Engine

- Instantly shows what's hot and where to aim
- Eliminates blind guesswork
- 24:1 spot size ratio for safer distance measuring

Grab and Go Simplicity


Fire It Up and Get to Work in Seconds

- Intuitive to operate with no special training required
- Easily save images and data for documentation
- Download images fast over USB or from removable micro SD


Rugged and Reliable

Designed for the Harshest Environments


- Built to withstand a 2 meter drop
- Covered by FLIR's exclusive 2-10 warranty
- Compact and durable to easily stow in a crowded tool bag




Electrical Troubleshooting



Warm Pipe in Wall



Mechanical Overheating



Refrigeration Issues

SPECIFICATIONS

| IR Temperature Measurement | |
|-----------------------------|---------------------------------------------------------------------------------------------------------------|
| Basic Accuracy | +/- 1.5% or 1.5°C |
| Range | -25 to 380°C, -13 to 716°F |
| Emissivity | 4 Pre-Set Levels with Custom Adjustment, 0.1 to 0.99 |
| Dist. to Spot Ratio (D:S) | 24:1 |
| Measurement Resolution | 0.1 °C / °F |
| Response Time | 150 Milliseconds |
| Spectral Response | 8 to 14µm |
| Lasers | Dual Diverging Lasers, Frames Temp Measurement Area |
| Thermal Imaging | |
| Imaging Detector | FLIR Lepton® Microbolometer Focal Plane Array (FPA) |
| Shutter | Integrated Automatic Shutter |
| Image Resolution (H x W) | 4,800 Pixels (80 x 60) |
| Spectral Response | 8 to 14µm |
| Field of View (H x W) | 50° x 38.6° |
| Upper Scene Range | 127°C, 260°F (400K) |
| Thermal Imaging Sensitivity | 150mK |
| Frame Rate | 9 Hz |
| Color Palettes | 2 (Grey Scale, Hot Iron) |
| Saved Image Format | Bitmap (BMP) Image with Temperature and Emissivity |
| General | |
| Unit Size (H x W x D) | 186 x 55 x 94 mm (7.3 x 2.2 x 3.7 in) |
| Display Type | 2.0 in TFT LCD |
| Display Resolution (W x H) | 38,720 Pixels (176 x 220) |
| Battery | Rechargeable via Micro USB Lithium-ion Battery: 3.7V, 2600mAh |
| Auto Power Off | Yes, Adjustable with Disable |
| Battery Life Hours | Typical Use: Five 8-Hr Work Days; Continuous Use: 8 Hrs |
| Certifications | CE / CB / FCC / FDA |
| Memory | 8Gb Micro SD Card |
| Operating Temperature | -10 to 45°C, 14 to 113°F |
| Drop Test | Designed for 2 Meter, 6.5 Feet |
| Tripod Mount | 1/4 in - 20 on Handle Bottom |
| Warranty | 2 Years Product, and 10 Years Thermal Imaging Detector when registered within 60 days of purchase. |
| Includes | Lanyard, USB Cable, International Charger (US, UK, EU, AU, CN) 8 Gb Micro SD Card, Technical Documentation |

ORDERING INFORMATION

| | |
|--------------|--------------------------------------|
| TG165 | Imaging IR Thermometer |
| TA13 | EVA Protective Case for TG165 |
| TA14 | Belt Holster for TG165 |

BELGIUM

FLIR Commercial Systems
Luxemburgstraat 2
2321 Meer
Tel. : +32 (0) 3665 5100
Fax : +32 (0) 3303 5624
E-mail : flir@flir.com

GERMANY

FLIR Systems GmbH
Berner Strasse 81
D-60437 Frankfurt am Main
Tel. : +49 (0)69 95 00 900
Fax : +49 (0)69 95 00 9040
E-mail : flir@flir.com

SWEDEN

FLIR Systems AB
Antennvägen 6
187 66 Täby
Tel. : +46 (0)8 753 25 00
Fax : +46 (0)8 753 23 64
E-mail : flir@flir.com

FRANCE

FLIR Systems France
20, bd de Beaubourg
77183 Croissy-Beaubourg
Tel. : +33 (0)1 60 37 55 02
Fax : +33 (0)1 64 11 37 55
E-mail : flir@flir.com

UNITED KINGDOM

FLIR Systems UK
2 Kings Hill Avenue - Kings Hill
West Malling
Kent
ME19 4AD
Tel. : +44 (0)1732 220 011
Fax : +44 (0)1732 843 707
E-mail : flir@flir.com

ITALY

FLIR Systems Italy
Via Luciano Manara, 2
I-20812 Limbiate (MB)
Tel. : +39 (0)2 99 45 10 01
Fax : +39 (0)2 99 69 24 08
E-mail : flir@flir.com

PORTLAND

Corporate Headquarters
FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
USA
PH: +1 866.477.3687

SPAIN

FLIR Commercial Systems
Avenida de Bruselas, 15- 3º
28108 Alcobendas (Madrid)
Tel. : +34 91 573 48 27
Fax. : +34 91 662 97 48
E-mail : flir@flir.com

MIDDLE EAST

Dubai Airport Free Zone
P.O. Box 54262
Office B-22, Street WB-21
Dubai - United Arab Emirates
Tel. : +971 4 299 6898
Fax : +971 4 299 6895
E-mail : flir@flir.com

RUSSIA

FLIR Systems Russia
6 bld.1, 1st Kozjevicheskoy lane
115114 Moscow
Russia
Tel. : + 7 495 669 70 72
Fax : + 7 495 909 93 02
E-mail : flir@flir.com

www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2014 FLIR Systems, Inc. All rights reserved. 091714